

## A346ECO, A546KECO, A756KECO



### TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous, placed into a protective housing in the back side of the vacuum cleaner
- Electric cable 10m long with industrial plug 3Ph+T 16A
- Star filter Ø460 with big surface on the models A346ECO and A546KECO
- Star filter Ø560 with big surface on the models A756ECO and A756KECO.
- Vacuum-meter to control the filter efficiency
- Manual filter shaker on top of the filter chamber
- Waste bin of 100l on castors with side handles and as option a clamp to have it up with the fork lift
- Quick inlet Ø70
- Painted version Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- Fixed wheels Ø150mm and revolving wheels with brake Ø125mm

		A346ECO	A546KECO	A756ECO	A756KECO
Tension /voltage	Volts	230-400V/50Hz	230-400V/50Hz	400/690V/50Hz	400/690V/50Hz
Power	Kw	2,2	4	5,5	5,5
Depression max	mbar max	300	400	480	400
Max working depression	mbar	200	200	420	275
Max air flow	m <sup>3</sup> /h	310	520	320	520
Primary filter surface	m <sup>2</sup>	1,90	1,90	3.4-Ø560	3.4-Ø560
Upstream absolute filter surface	m <sup>2</sup>	2,20	2,20	No	No
Container capacity	Lt	100	100	100	100
Product inlet	mm	Ø70	Ø70	Ø70	Ø70
Noise level	DbA	74	76	73	73
Overall dimensions	Cm	65X110X152H	65X110X152H	65x120x175h	65x120x175h
Weight	Kg	102	135	170	170
Protection	IP	54	54	54	55