

## A63M



### TECHNICAL FEATURES:

- Machine body Ø460mm
- Side channel blower exposed to view with single phase motor asynchronous
- Electric cable 9m long with Schuko plug
- Manual filter shaker on side
- Star filter of polyester cat. "L" - Ø460mm
- Quick inlet Ø70mm
- 65l waste bin with integrated handle and castors
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with trolley Ral 9005 (black), container and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- X2 version with waste bin and filter chamber in stainless steel
- Available with motor housing in painted version Ral7001 (grey) and in stainless steel
- We recommend using accessories of Ø40mm and Ø50mm

|                         |                   | A63M       |
|-------------------------|-------------------|------------|
| Tension /Voltage        | Volts             | 1X230/50Hz |
| Power                   | Kw                | 2.2        |
| Depression max          | mbar max          | 300        |
| Max working depression  | mbar              | 220        |
| Max air flow            | m <sup>3</sup> /h | 310        |
| Primary filter surface  | m <sup>2</sup>    | 1,90       |
| Absolute filter surface | m <sup>2</sup>    | 2,20       |
| Container capacity      | Lt                | 65         |
| Product inlet           | mm                | Ø70        |
| Noise level             | DbA               | 75         |
| Overall dimensions      | Cm                | 64x73x162h |
| Weight                  | Kg                | 78         |
| Protection              | IP                | 55         |