

ONE32, ONE33, ONE62, ONE63
ONE102, ONE103



- TECHNICAL FEATURES:**
- Machine body Ø460mm
 - Single-phase brush motors double stage by-pass
 - Motor-head in sound-proof ABS and metal
 - Independent switches for each motor
 - Vacuum-meter and red light to control filter efficiency
 - Electric cable 9m. long with Schuko plug
 - Manual filter shaker on top of the head
 - Star filter in polyester cat. "L"- Ø460mm
 - Quick product inlet Ø70mm
 - Waste bin of 39 or 65 l with integrated handle and castors
 - Waste bin of 100 l with side handles and castors
 - Rear castors Ø150mm, front castors Ø125mm with brake
 - Painted version with trolley Ral 9005 (black), waste bin and filter chamber Ral 7001 grey
 - X1 version with waste bin in stainless steel
 - X2 version with bin and filter chamber in stainless steel
 - We recommend using cleaning accessories Ø40mm and Ø50mm

		ONE32	ONE33	ONE62	ONE63	ONE102	ONE103
Tension/Voltage	Volts	1Ph 230V/50-60Hz	1Ph 230V/50-60Hz	1Ph 230V/50-60Hz	1Ph 230V/50-60Hz	1Ph 230V/50-60Hz	1Ph 230V/50-60Hz
Power	Watt	2200	3300	2200	3300	3300	3300
Depression max	mbar	210	210	210	210	210	210
Max air flow	m³/h	340	510	340	510	340	510
Primary filter surface	m²	1.90	1.90	1,90	1,90	1,90	1,90
Absolute filter surface	m²	2.20	2.20	2,20	2,20	2,20	2,20
Container capacity	Lt	39	39	65	65	100	100
Product inlet	mm	Ø70	Ø70	Ø70	Ø70	Ø70	Ø70
Noise level	Dba	73.80	74.30	73.80	74.30	73.80	74.30
Overall dimensions	Cm	78X64X121	78X64X121	78X64X135	78X64X135	78X64X156	78X64X156
Weight	Kg	54	56	56	58	60	62
Protection	IP	44	44	44	44	44	44