

ONE 21 & ONE22



TECHNICAL SPECIFICATIONS:

- machine body Ø360mm
- Single phase brush motor double stage by-pass
- Motor-head in ABS/metal black coloured
- Independent switches for each motor
- Vacuum-meter to check the filter efficiency
- Electric cable 9m. long with Schuko plug
- manual filter shaker on top of the vacuum
- Star filter in polyester cat. "L"
- Quick inlet Ø70mm
- Dust bin of 25 l. provided with handle and castors
- Rear castors Ø125mm, front castors Ø100mm with brake
- Painted version with trolley in Ral 9005 (black), container and filter chamber in Ral 7001 (grey)
- X1 version with dust bin in stainless steel
- X2 version with dust bin and filter chamber in stainless steel
- X3 version with dust bin, filter chamber and trolley in stainless steel but motor-head in painted/ABS
- We recommend using cleaning accessories Ø40mm for 1-motor versions and Ø50mm for 2-motors versions

		ONE21	ONE22
Tension /Voltage	Volts	1Ph 230V/50-60Hz	1Ph 230V/50-60Hz
Power	Watt	1100	2200
Depression max	mbar	210	210
Max air flow	m ³ /h	170	340
Primary filtering surface	m ²	0,70	0,70
Absolute filtering surface	m ²	1,20	1,20
Container capacity	Lt	25	25
Product inlet	mm	Ø70	Ø70
Noise level	dB(A)	76	78
Overall dimensions	Cm	48x63x104h	48x63x104h
Weight	Kg	30	32
Protection	IP	44	44