

ONE72SUBOIL-ONE73SUBOIL



TECHNICAL FEATURES:

- Machine body Ø460mm
- Head made of metal with 2 or 3 single phase brush motors double stage by-pass
- Independent switches for each motor
- Centrifugal discharge pump, single phase, with open rotor to empty the liquid, power 0.55kw, delivered quantity of 200 l/min. with water
- Electric cable 9m with Schuko plug
- Filter for oil mists Ø460mm
- Filter of polyester oil proof cat. "M"
- Quick inlet Ø50mm
- Container for liquids with 70 l. capacity
- Container for shaving with 20 l. capacity
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with frame Ral 9005 (black) containers both for liquids and shaving Ral 7001 (grey)
- X2 version with containers, both for liquids and shaving, in stainless steel
- Accessories for cleaning NOT included in the supply, the only item supplied is the bent connection code 65229

		ONE72SUBOIL	ONE73SUBOIL
Tension/ Voltage	Volts	1x 230V/50Hz	1x 230V/50Hz
Power	Watt	2750 (2200+550)	3850 (3300+550)
Depression max	mbar	210	210
Max air flow	m ³ /h	340	510
Primary filter surface	m ²	0.20	0.20
Liquid expulsion pump flow rate (with water)	lt/m	200	200
Container capacity for liquids	Lt	70	70
Container capacity for chips	LT	20	20
Product inlet	mm	Ø50	Ø50
Noise level	DbA	77	77
Overall dimensions	Cm	70X65X142H	70X65X142H
Weight	Kg	62	64
Protection	IP	44	44